

# **Porcelain Stoneware Impregnation**

## Feinsteinzeug Impraegnierung

#### Description

Protects against oily, greasy and water-based contamination. For polished, matte, ground and structured fine stoneware in indoor and outdoor areas. Can also be used as joint protection.

#### Action

Impregnates surfaces permanently and protects invisibly against contamination and traces of usage. The treated surface is easy to clean and protected against future contamination, e.g. through oil, grease and water stains.

## Scope of application

For all surfaces of polished, matte, ground and structured fine stoneware or stoneware in indoor and outdoor areas.

For treatment of tables, walls, floors or worktops. Can also be used for porous surfaces such as concrete joints.

## **Application**

Apply on dry surface only. The surface must be cleaned before hand.

Apply the undiluted impregnation thinly but covering using a paint roller or brush.

The efficiency can be enhanced by a further weton-wet application. In the process, do not apply more impregnation than can be absorbed by the surface.

Leave it to soak 50 minutes after application. Remove excess liquid using an absorbent dry cloth. No streaks should remain. Dried residues can be removed with a cloth which has previously been soaked with impregnation. The subsequent impregnation drying time is 3-4 hours. The surface should not be accessed and there should not be any damp treatment during this drying time.

Full effect is given after 24 hours.

#### Note:

Always work in sections on large areas. Cover glass and surfaces sensitive to solvents during the application. When used as joint protection, apply only onto clean, stain-free and through-hardened joints. Otherwise this may result in unevenness and discoloration.

#### Technical data

- Density: 0.78-0.80 g/ml

- pH value: n.a.

- Appearance: light yellow liquid

- Odour: mild

## Consumption/range

- Sufficient for 40-60 m<sup>2</sup>

### Safety notes

- Harmful
- Harmful: may cause lung damage if swallowed.
- Repeated exposure may cause skin dryness or cracking.
- Keep out of the reach of children.
- Do not inhale vapour.
- Avoid contact with skin.
- If swallowed, do not induce vomiting.
- Seek medical advice immediately and show this container or label.

Info Telephone: +49 (0) 55 41 / 70 03 - 491

## Packaging unit

1000 ml metal canister (4 pcs. in carton)

Order no. 390 353

There is a huge diversity of application conditions and areas of applications of our products. Therefore, we can only give general instructions for use in the product information concerned. They can and shall only give general advice. Check and adapt the use of the products to local conditions and the surfaces to be treated. Always pre-test the products on an inconspicuous area in all cases of doubt or in absence of experience. We would be happy to offer you advice if you have special requirements.

We shall only be liable for incomplete or incorrect technical data in case of gross default on our part (wilful misconduct or gross negligence).